

ZERUST® ActivDri™ Capsule protects ferrous and aluminum metals in enclosed spaces. It utilizes Vapor Corrosion Inhibitors (VCIs) to prevent corrosion and a silica-gel desiccant to combat humidity that affects metals and electronics. It is designed to protect large voids inside critical items during shipping and storage.

The ActivDri™ Capsule features a durable coated steel cable to aid in inserting and retrieving the unit from the center of a void space. The cable is affixed to the capsule at multiple points to provide a secure hold. When the protected item is ready for service or final assembly, simply remove the capsule.

Use ActivDri[™] to protect electronics, equipment, and assets in corrosive environments such as salty air, sewage treatment plants, or power plants. ActivDri[™] corrosion inhibitors form an invisible shield that provides powerful corrosion protection. The capsule reduces flash-rust and corrosion incidents, even in contaminated and challenging environments. Do not place the capsule in direct contact with yellow metals, and test before use with copper and brass.

Application Example

ZERUST® ActivDri™ protects large enclosures such as electronic housings and gearboxes for up to one year from corrosion.



▶ Be

Benefits

Reduces corrosion incidents

Improves equipment reliability and readiness

Reduces the need for inspection & rework

Saves money & resources

Comes with ZERUST® global onsite support

Application Type

Inventory
Export Shipment
Long-Term Storage











Availability

ZERUST®/EXCOR® ActivDri™ FAD12-1 Capsules are sold in cases of 10 units. Call for availability.

Part Number	Quantity	
375-F-00003	10/Case	

Description	ZERUST® ActivDri™ Capsule is a (VCI) Vapor Corrosion Inhibitor diffuser with silica-gel desiccant.			
Appearance	ance PE-plastic capsule and foam or protective foam containing active pellets.			
Protected Metal Types	Ferrous and aluminum protection. Protects yellow metals when used as instructed. Do not place in direct contact with copper, brass, or zinc, and test before use.			
Protection Duration and Volume	See table below			
Storage	Store in a cool 85°F (30°C), dry place and away from sunlight in original packaging for up to 2 years from			

Protection Capabilities*

temperatures.

	Corrosion Protection		
ZERUST® Product Name	Volume of Protection (Up to)	Duration of Protection (Up To)	Silica Gel (Up To)
ActivDri™ FAD12-1	177 ft³ (5 m³)	1 year	7 oz. (200 g)

the date of shipment. The product may expand at high

DECLARATION

This Data sheet and information it contains is considered to be accurate at the date of printing. No representation or warranty, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. **LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on validations and tests conducted by Northern Technologies International Corporation/ZERUST® or its partners and are believed to be reliable, but the accuracy or completeness thereof is not guaranteed. We warrant our products will be free from defects when shipped to customer. Our obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Northern Technologies International Corporation/ZERUST® or its partners or agent of the claimed defect within 3 months after shipment of product to customer. Customer shall pay all freight charges for replacement products. We shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. And any financial claims shall be limited to the value of the film sold. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of the company. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose. In no case shall Northern Technologies International Corporation/ZERUST® be liable for incidental or consequential damages.

For full warranty and disclaimer information visit, www.zerust.com/warranty.

@2013-2023 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor Tab®, EXCOR®, Flange Saver®, ICT®, Natur-VCI®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, 洁乐特, Z-PAK® and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

•

Precautions

- Do not place in direct contact with copper, brass, or zinc, and test before use.
- Do not install the capsule where it will be submerged in water.
- Dispose of in accordance with local regulations.

Contact Us



A product of: Northern Technologies International Corp 4201 Woodland Road Circle Pines, MN 55014

Phone. +1 763.225.6600 Fax. +1 763.225.6645 sales@zerust.com www.zerust.com

^{*}Specifications are rated for an airtight enclosure with a relative humidity level of less than 40%. For more humid, contaminated, and/or frequently accessed enclosures, use multiple capsules or replace them more often.