

ZERUST®/EXCOR® AxxaVis™ PX-05-AN is a powder, that when added to rinse water, enables it to neutralize acids left by cleaning processes. Use as a final rinse to control flash corrosion on metals caused by acidic cleaning treatments, such as acid pickling and ZERUST® AxxaClean™ rust removal products.

Add AxxaVis<sup>™</sup> PX-05-AN to water used as a rinse after cleaning metals with ZERUST® AxxaClean<sup>™</sup> rust removers or acid pickling. A solution of AxxaVis<sup>™</sup> PX-05-AN reduces flash corrosion caused by issues from acids, especially on highly reactive surfaces such as cast iron.

To use, dilute AxxaVis™ PX-05-AN in deionized water. When using tap sources, pretreat water with ZERUST® AxxaVis™ PX-10-HRD. Spray or dip freshly cleaned parts in the AxxaVis™ PX-05-AN water solution and rapidly dry. Place items into ZERUST®/EXCOR® VCI corrosion inhibitor packaging or rust preventatives for shipping or storage.

## **Dosage Instructions**

Water*	AxxaVis™ PX-05-AN
1L of purified water	Add depending on application Typically 10 -100 g/L or 1-10% by weight

<sup>\*</sup>For water with a hardness above 100 ppm, pre-treat with ZERUST® AxxaVis™ PX-10-HRD.

## **Application Example**

Highly reactive cast iron parts recently cleaned by an acidic rust remover were rinsed with a solution of AxxaVis™ PX-05-AN. Items were then placed in packaging using ZERUST® VCI Kraft paper.





Controls flash corrosion

Neutralizes acids

Use as a spray or immersion

Safe and non-hazardous\*



Part Number	Quantity
460-F-00005	25 lb case

## Product Info

- \*Safe to use and handle. Product is not hazardous for people or the environment according to EU (CLP) or OSHA HazCom 2012 (US GHS).
- For use with ferrous metals. Multimetal compatible. Not recommended for extended exposure to aluminum.

Northern Technologies International Corp 4201 Woodland Road, Circle Pines, MN 55014 USA Phone. +1 763.225.6600 / Fax. +1 763.225.6645 sales@zerust.com / www.zerust.com



Warranty and Disclaimer Information: We guarantee our products conform to documented quality specifications. Product information subject to change without notice. We make no warranty of any kind expressed or implied as to the effects of use (including, but not limited to, damage or injury). For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2013-2023 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor Tab®, EXCOR®, Flange Saver®, ICT®, Natur-VCI®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, 浩东特, Z-PAK® and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner