
ZERUST[®] ICT[®]520-CB1 Anti-Tarnish Film

ZERUST[®] ICT[®]520-CB1 Anti-Tarnish scavenger film blocks out the corrosion-causing acid gases before they can cause damage to metals. ZERUST[®] Anti-Tarnish film and bags contain ZERUST[®] acid-gas scavengers that protect silver and yellow metals against oxidation and tarnish.

Marth.

ZERUST[®] ICT[®]520-CB1 Anti-Tarnish film protects silver, copper, bronze, brass, or tin from unsightly and damaging oxidation and tarnish. Typical applications include silver items, copper wiring, electronic components, and musical instrument strings. When used in conjunction with other ZERUST[®] technologies, it will provide added protection for all metal types while preventing acid gases from entering the packaging. In addition, ZERUST[®] does not leave any residues or affect the functionality of protected items.



Safe* for employees, customers, and the environment

No cleaning of parts is required when removed from bag


Lightweight design makes transportation & handling easier

Can be colored to the customer's specifications

Application Examples

ZERUST 🛟 EXCOR

Circuit board packaged in ZERUST[®] ICT[®]520-CB1 Anti-Tarnish film.







Application Type

Export Shipment Long-Term Storage Inventory Storage Work-In-Progress

> *Safe for people. This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom, and CA WHMIS regulations.

Zerust



Product Information

Description	ZERUST [®] ICT [®] 520-CB1 Anti-Tarnish Film is an odorless Transparent polyethylene Film impregnated with acid-gas scavengers.
Appearance	Typical color is transparent. Additional colors available are upon request.
Protected Metal Types	Protects silver, copper, bronze, brass, and tin from oxidation and tarnish.
Protection Duration	Objects can be protected for years when properly packed, sealed, and utilized within three years from receipt. Not intended for outdoor use.
Storage	Store in original packaging away from direct sunlight in

conditions below 85°F (30°C) and 50% RH for up to 3 years from the date of shipment.

Property	Direction (Machine or Transverse)	ZERUST® ICT®520- CB1Anti-Tarnish Film*	ASTM Test Method
Film Thickness	-	4mil (102 µm)	D-6988
Dart Impact Resistance	-	300 g	D-1709
Tear Strength	MD	0.60 lb-f (2.7 N)	D-1938
	TD	0.65 lb-f (2.9 N)	
Tensile Strength	MD	1905 psi (13.1 MPa)	D-882
at Yield	TD	1538 psi (10.6 MPa)	
Tensile Strength	MD	3045 psi (21.0 MPa)	D-882
at Break	TD	2917 psi (20.1 MPa)	D-002
Elemention at Break	MD	560%	D-882
Elongation at Break	TD	610%	
Drooking Factor	MD	11.0 lb-f/in (1926 N/m)	D-882
Breaking Factor	TD	11.5 lb-f/in (2014 N/m)	
Water Vapor Transmission Rate @78°F (26°C), 90% RH	-	0.06 g/(100 in²/day)	F-1249
Vapor Inhibiting Ability (VIA)	-	Pass	NACE TM0208


* Typical values, not meant to be a specification.

DECLARATION

This Data sheet and information it contains is considered to be accurate at the date of printing. No representation or warranty, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. **LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on validations and tests conducted by Northern Technologies International Corporation/ZERUST® or its partners and are believed to be reliable, but the accuracy or completeness thereof is not guaranteed. We warrant our products will be free from defects when shipped to customer. Our obligation under this warrant y shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Northern Technologies International Corporation/ZERUST® or its partners or agent of the claimed defect within 3 months after shipment of product to customer. Customer shall pay all freight charges for replacement products. We shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. And any financial claims shall be limited to the value of the product sold. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of the company. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose. In no case shall Northern Technologies International Corporation/ZERUST® be liable for incidental or consequential damages. For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2013-2023 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor Tab®, EXCOR®, Flange Saver®, ICT®, Natur-VCI®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, 洁乐特, Z-PAK® and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.



ZERUST[®] ICT[®]520-CB1 Anti-Tarnish Film is available in 2.0 mil-6 mil thickness, custom sizes, and additive options such as UV and anti-static. Contact a ZERUST[®] account manager for pricing and availability.

Recyclable

Dispose of in accordance with local, national, and international regulations. Check on options for recycling and incineration.

Safety

 Safe for people. This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom, and CA WHMIS regulations.

A product of: Northern Technologies International Corp 4201 Woodland Road Circle Pines, MN 55014 USA

Phone. +1 763.225.6600 Fax. +1 763.225.6645 sales@zerust.com